

Material Safety Data Sheet

1. Product Name: Perma-Deck®

2. Description: These products are made of 100% recycled plastic.

3. Composition: Post-consumer and post-industrial recycled plastic.

Physical state	Solid
Specific gravity	56 lb./ ft ³ - 58 lb./ ft ³ (897.03 kg./ m ³ - 929.07 kg./ m ³)
Boiling point	NA: solid material
Vapour pression	NA: non-volatile material
Vapour density	NA: non-volatile material
Coefficient of oil / water distribution	Insoluable in oil and water
Melting point	240 °F – 260 °F

4. Fire Hazard Data:

Flash point	NA
Auto ignition temperature	630 °F – 770 °F
Flammability limit	Non-volatile material

Fire extinguishing substances: Water spary, foam, dry chemical extinguisher.

Hazardous combustion products: Carbon monoxide formation is enhanced under oxygen starvation conditions. Organic vapours are possible when a fire exists.

5. Reactivity Data:

Stability	Stable
Incompatibility	None

6. Health / Safety Information:

Standard Personal safety equipment (safety glasses, gloves, etc...) is suggested when working with material (drilling, sawing, etc...). May contain very small amounts of non-ferrous soft metal particles. This small particuls do not represent any danger when adequat standard personnal safety equipment is used.

7. Manufacturer:

Produits Re-Plast inc.
1350 Chemin Quatre-Saisons
Notre-Dame du Bon-Conseil, Québec
J0C 1A0

Telephone : (819) 336-2440
Fax : (819) 336-2442